



1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1

PCT

(10) International Publication Number
WO 02/32293 A2

(51) **International Patent Classification⁷:** **A61B** (74) **Agents:** HONAKER, William, H. et al.; Howard & Howard Attorneys, P.C., 39400 Woodward Avenue, Suite 101, Bloomfield Hills, MI 48304-5151 (US).

(21) **International Application Number:** PCT/US01/47317

(22) **International Filing Date:** 3 October 2001 (03.10.2001)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
09/692,928 20 October 2000 (20.10.2000) US
09/776,444 2 February 2001 (02.02.2001) US

(71) **Applicant:** IMAGYN MEDICAL TECHNOLOGIES CALIFORNIA, INC. [US/US]; One Park Plaza, Suite 110, Irvine, CA 92614 (US).

(72) **Inventors:** WORM, Dustin; 6116 Duernsey Lake Road, Delton, MI 49046 (US). FLATLAND, Martin; 533 Grand Pre, Kalamazoo, MI 49006 (US). TOMANDL, Mark; 436 W. Colfax Street, Hastings, MI 49056 (US). PENROD, Mark, A.; 150 Pifer Road, Delton, MI 49046 (US). LUN, Warren, D.; 175 South Kendall Street, Battle Creek, MI 49015 (US).

(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 02/32293 A2

(54) Title: INCISIONAL BREAST BIOPSY DEVICE

(57) Abstract: A biopsy device is provided which includes a localization needle having a guide wire preloaded into the biopsy device. The device includes a stylet having a blade for transecting and separating tissue. The device further includes a cannula for cutting a core of tissue and a garrote wire mechanism for cutting a transection of tissue transverse to the core cut by the cannula. The garrote wire is activated by a trigger mechanism which is locked out by a lockout feature within the device until the garrote wire has been advanced around the core of tissue cut by the cannula.

5

INCISIONAL BREAST BIOPSY DEVICE**BACKGROUND**

This invention relates generally to surgical instruments and, more particularly, to a device for percutaneous incisional breast biopsy.

The early diagnosis of breast cancer through the use of mammography is very important for reducing the morbidity associated with breast cancer. Early diagnosis enables a physician to treat the breast cancer at a more manageable stage of development. Mammography is capable of detecting very small abnormalities in breast tissue. However, mammography usually cannot differentiate between malignant and benign lesions in the breast. Definitive determination of the status of a lesion often requires a histological examination of the suspect tissue.

One method for obtaining a tissue sample for histological examination is through a biopsy of part or all of the suspect tissue. There are a number of devices and methods for performing a biopsy of the breast. Generally, the procedure requires first placing a localization needle within or near the lesion. A guide wire contained within the localization needle is then deployed. The guide wire usually includes hooks that anchor one end of the guide wire in breast tissue near the lesion. Then a biopsy device that includes a cannula and a stylet located within the cannula is inserted over the localization needle and guide wire. The device is inserted through a small incision in the breast tissue near the entry point of the localization needle. The stylet bluntly separates breast tissue as the device is inserted over the guide wire toward the lesion. Advancement of the device is stopped once the tip of the stylet is within or near the lesion. Then, the cannula, which has a cutting surface at a leading edge, is advanced over the stylet and into the tissue thereby cutting a core of tissue. The cutting surface is advanced to a point beyond the end of the guide wire. Then, a second cutting surface, typically a wire garrote, is activated to perform a cut transverse to the core and to a longitudinal axis of the cannula creating a tissue sample. Then the needle, guide wire, and device are retracted from the breast with the tissue sample. The tissue sample is then histologically examined to determine whether the suspect tissue is malignant or benign.

5 The current biopsy devices have a number of disadvantages including that
the device, localization needle, and guide wire are not manufactured as a single unit,
also the devices generally do not have a means for insuring that the garrote wire is
located past the end of the guide wire prior to deployment of the garrote. To
determine whether the garrote is located past the end of the guide wire with a typical
10 biopsy device, a radiographic check is required. Finally, the typical blunt stylet
requires substantial force to insert and may cause trauma to the healthy tissue as it
passes to the biopsy site.

Therefore, it is desirable to provide a biopsy device manufactured as an integrated unit having a localization needle and a guide wire. Additionally, it is desirable to provide a biopsy device having features to insure that the garrote wire is not deployed until it is past the end of the guide wire. It is also desirable to provide a stylet with cutting members to cleanly transect and separate breast tissue and minimize the damage to healthy tissue.

20 SUMMARY OF THE INVENTION

The present invention overcomes the problems with previous biopsy devices by providing a biopsy device which is manufactured with an integral localization needle and guide wire. In addition, the invention includes structure to insure that the garrote wire is not deployed until the garrote wire is beyond the end of the guide wire. Further, the stylet is provided a blade which transects tissue as the device is inserted to the biopsy site.

According to one aspect of the present invention, the device includes a cannula having a shaft with a cutting surface on one end of the shaft and the other end of the shaft in engagement with a drive assembly. Adjacent to the cutting surface of the cannula is a second cutting mechanism for making a cut transverse to a cut made by the shaft cutting surface. Located within the cannula shaft is a stylet. The stylet has a tip portion with a blade for transecting and separating tissue and a central chamber for permitting a localization needle to pass through the length of the stylet. The localization needle has an interior chamber permitting passage of a guide wire through the length of the localization needle. The device also includes a lock

- 5 feature for preventing deployment of the second cutting mechanism until it is past the end of the guide wire.

According to a further aspect of the present invention, a method of removing suspect breast tissue with a breast biopsy device includes the steps of inserting a localization needle into tissue, advancing a hooked guide wire out of a distal end of the localization needle to anchor the biopsy device in the tissue in or near a lesion,
10 the localization needle to anchor the biopsy device in the tissue in or near a lesion, advancing a stylet and cannula over the localization needle until the stylet is adjacent the lesion, advancing a cannula shaft cutting surface to cut a core of tissue, unlocking a trigger of a garrote when a cutting plane of the garrote has been advanced past a distal end of the guide wire, and moving the trigger to activate the
15 garrote and make a cut transverse to the direction of advancement of the cannula shaft.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of a biopsy device designed according to the
20 invention mounted on an instrument holder;

Figure 2A is an exploded view of a stylet of the present invention;

Figure 2B is a side view of the stylet end.

Figure 2C is a side view of the stylet end rotated 90° from the position in
figure 2B.

25 Figure 3 is a perspective view of of the stylet entering a tissue sample;

Figure 4 is a perspective view of the stylet and a localization needle and a guide wire entering the tissue sample;

Figure 5 is a perspective view of the localization needle and the guidewire inserted into the tissue sample and the stylet retracted within a cannula of the biopsy
30 device;

Figure 6 is a perspective view of the cannula cored into the tissue sample;

Figure 7 is a perspective view of the cannula with a portion of the tissue pulled into the cannula by the guidewire;

Figure 8 is an exploded view of a cannula assembly;

5 Figure 9 is an exploded view of the biopsy device with an upper and lower housing removed;

 Figure 10A is a top view of the biopsy device with the upper housing removed and the cannula shaft in a retracted position;

 Figure 10B is a top view of the biopsy device with the upper housing
10 removed and the cannula shaft in an extended position;

 Figure 10C is a top view of the biopsy device with the upper housing removed and the trigger partially deployed;

 Figure 10D is a top view of the biopsy device with the upper housing removed showing full deployment of the trigger;

15 Figure 10E is a top view of the biopsy device with the upper housing removed showing resetting of the trigger;

 Figure 10F is a top view of the biopsy device with the upper housing removed and shown after completion of a transection of the tissue sample;

 Figure 11 is an exploded view of an alternative cutting mechanism housed
20 within the cannula;

 Figure 12A-12B are side views of an alternative garrote wire mechanism including an inner and outer sleeve shown prior to and during deployment, respectively;

 FIG 13A-13B are side and cross-sectional views, respectively, of an
25 alternative garrote wire mechanism including a first and a second independent sleeve;

 FIG 14 is a cross-sectional view of an alternative garrote wire mechanism including a first and second sleeve interconnected by a spring; and

 FIG 15 is a perspective view of an alternative garrote wire mechanism
30 comprising a wire spool mechanism.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Referring to the Figures wherein like numerals indicate like or corresponding parts throughout the several views, in Figure 1 a biopsy device is shown generally at
35 10. The device 10 is shown mounted on an instrument holder 140. The instrument

holder 140 includes a housing 142 and rotation knob 144 mounted within the housing 142. A bracket 146 connects the housing 142 to a track 148. The track 148 can be fixed to a point along a rail (not shown) by a friction cam brake (not shown). The device 10 includes a housing 11 having a trigger slot 25. A trigger 26 extends through the trigger slot 25. A stylet retracting knob 56 is mounted adjacent a front end 9 of the housing 11 and connected to a stylet tube 52 (See Figure 2A). A localization needle 62 passes through the stylet retracting knob 56 and through the stylet tube 52. A hub 64 is mounted on a distal end of the localization needle 62.

A guide wire 66 is slidably received within the localization needle 62. A stop 68 is mounted on one end of the guide wire 66. A cannula 14 extends from a front end 9 of the housing 11. A stylet 18 is mounted on the stylet tube 52 and the stylet 18 extends beyond the end of the cannula 14 when the stylet tube 52 is extended and the cannula 14 is retracted.

In Figures 2A-2C the stylet 18 is shown in greater detail. The stylet 18 comprises a first blade 16 and a second blade 17 integrated between two halves of a stylet housing 21 onto an end of the stylet tube 52. The stylet housing 21 is preferably cone shaped with the first blade 16 and the second blade 17 exiting the cone. The stylet 18 transects, dilates, and separates tissue as the device 10 is inserted toward the biopsy site. In a preferred embodiment a leading edge 27 of the stylet housing 21 forms a forty five degree angle with the center axis 29 of the stylet housing 21. The leading edge 27 is then radiused at 31 into the body 33 of housing 21. Body portion 33 is generally parallel to the center axis 29. The first blade 16 and the second blade 17 are exposed in a curved fashion from an end 31 of the stylet housing 21 and extend to the center axis 29 of the stylet housing 21.

With reference to Figures 3-7, the biopsy device 10 is shown in various stages of deployment. First an incision 6 is made in the external surface of a breast tissue 5 adjacent a tissue lesion 7, the localization needle 62 is inserted into the lesion 7, and the guidewire 66 located within the localization needle 62 is deployed to anchor the biopsy device 10 in the lesion 7. Preferably, the guidewire 66 consists of a single wire with a barb 67 for marking, stabilizing, and holding the lesion 7. Alternatively, the guidewire 66 may consist of two or more wires and two or more

5 barbs 67 for increasing the holding ability of the guidewire 66 in various densities of
the breast tissue 5. The cannula 14 and the stylet 18 are then advanced over the
localization needle 62 with the stylet 18 and blades 16, 17 transecting and separating
the healthy breast tissue 5 with minimal trauma to the healthy tissue as the cannula
14 is inserted toward the lesion 7. The cannula 14 is then simultaneously advanced
10 and rotated to core lesion 7. A cutting ring 70 is mounted within the cannula nose of
the cannula 14 to provide the cutting action as the cannula 14 is extended. Once the
core of lesion 7 has been cut a garrote wire cutting mechanism, as described below,
is deployed to transect the tissue core creating an excised sample of tissue.

Figure 8 shows an exploded view of cannula 14 and Figure 9 shows an
15 exploded view of the device 10. A garrote wire 74 having a looped section 75 that
acts as a cutting surface is provided within the cannula 14. A center portion 77 of
the garrote wire 74 extends from the looped section 75 into recessed garrote tubes 78
located on a side of the cannula 14. The garrote wire 74 exits the garrote tubes 78
and then proceeds into an opening 78a in the cannula 14. The garrote wire 74 then
20 proceeds through an opening 94 in shaft 22 and continues through a hole 96 in a
spline gear 36 and through a notch 98 in a stop ring 38. A first end of the garrote
wire is attached to a trigger plunger 40. A second end of garrote wire 74 is attached
to the spring plunger 48. In the disclosed embodiment, an end cap 87 covers the end
of cannula 14. The trigger plunger 40 is activated by movement of a trigger body 24
25 that is connected to trigger 26 and is used to activate the garrote wire 74 and cut the
tissue plug in a direction transverse to the direction in which the cannula 14 was
advanced. When the trigger 26 is pulled, the trigger body 24 engages the trigger
plunger 40 causing trigger plunger 40 to move and pull one side of garrote wire 74.
As plunger 40 moves, it engages and compresses spring 46 against spring plunger
30 48. Since spring plunger 48 can move with respect to trigger plunger 40, the side of
the garrote wire 74 attached to spring plunger 48 can move in the opposite direction
to the side of the garrote wire 74 attached to trigger plunger 40. In this way, there is
a slight sawing action of the garrote wire 74.

The trigger 26 is provided with a locking mechanism, comprising a pair of
35 trigger lock ramps 34 and a lock depressor 42, for preventing deployment of the

5 garrote wire 74 prior to movement of a cutting plane of the garrote wire 74 past an
end of the guidewire 66. The lock ramps 34 have a distal end 200 and a proximal
end 210. The proximal end 210 is attached to the lower housing 58 at attachment
points 220. The distal end 200 of lock ramps 34 is a free end and is adjacent a
surface 250 of the trigger body 24 keeping the trigger body 24 from moving in a
10 direction toward the lock ramps 34. In an undepressed state the distal end 200 is
located at a height greater than that of the proximal end 210 relative to the housing
58. The lock depressor 42 is slidably mounted on a surface 230 of lower housing 58
and is connected to the trigger plunger 40 through a raised portion 240 of the lock
depressor.

15 In application, as the cannula 14 is advanced to cut a core of tissue 5 and
lesion 7 the trigger plunger 40 is advanced along the shaft 22 and thereby advances
the lock depressor 42 along the lock ramps 34 depressing the distal end 200 of the
lock ramps 34. This process continues until the cannula 14 has been advanced a
predetermined distance to a point whereby the cutting plane of the garrote wire 74
20 contained within the cannula 14 has been advanced beyond the guide wire 66 and
is thereby clear to make a cut. At this point, the distal end 200 of the lock ramps 34
are fully depressed by the lock depressor 42 and allow the trigger body 24 to move
over the ramps 34 to deploy the garrote wire 74.

 In a preferred embodiment of cannula 14 as shown in Figure 8, the cannula
25 14 contains a distal disk blade 72 and a proximal disk blade 76 providing cutting
surfaces in addition to cutting ring 70 to assist the garrote wire 74 in transecting the
lesion 7. Alternatively, the cannula 14 could contain a plurality of additional blades.
In this embodiment the garrote wire 74 exits the cannula 14 through a notch 80 in
the proximal disk blade 76 and the looped section 75 of the garrote wire 74 is
30 located between the proximal disk blade 76 and the distal disk blade 72.

 In operation, the garrote wire 74 pulls the lesion 7 against the disk blades 72
and 76 to facilitate cutting of the lesion 7. Since the garrote is positioned between
blades 72 and 76, the lesion 7 is pulled against the blades 72 and 76 which cuts into
the lesion. By pulling the trigger 26, the garrote wire 74 cuts through one side of the
35 lesion 7 as the blades 72 and 76 cut through the opposite side.

5 In Figure 9, a drive assembly 82 is shown mounted within the housing 11. Housing 11 includes an upper housing 12 and a lower housing 58. The drive assembly 82 includes a cylindrical shaft 22 with a proximal end 88 and a distal end 86. The distal end 86 of shaft 22 has a larger diameter than the proximal end 88. A portion of shaft 22 beginning at the proximal end 88 contains a spline 84 for
10 mounting the spline gear 36. A screw base 90 is formed within the lower housing 58. A lead screw 50 is mounted to the screw base 90 and extends into an internally threaded portion of the proximal end 88 of the shaft 22, thereby supporting the proximal end 88 of the shaft 22. A shaft housing 192 is formed in an end of lower housing 58 and supports the distal end 86 of shaft 22. A drive gear 32 is mounted
15 within the lower housing 58 and engages the spline gear 36. In use, the drive gear 32 is driven by rotation of the rotation knob 144 and in turn drive gear 32 rotates the spline gear 36. Rotation of the spline gear 36 advances the shaft 22 down the lead screw 50. Movement of the shaft 22 advances and rotates the cannula 14 into the tissue which cuts a core of tissue as the cutting ring 70 rotates and advances. A
20 compression spring 46 is mounted around the shaft 22 and is held at one end by a clip 44 and at another end by a spring plunger 48. Located between the clip 44 and the spline gear 36 are the stop ring 38 and the trigger plunger 40. The triggers 26 are connected to the trigger body 24 by a pair of shoulder screws 28. The trigger body 24 rides on two trigger rods 30 mounted in lower housing 58 and contains an
25 opening 100 which allows the trigger body 24 to engage the trigger plunger 40. Both the trigger body 24 and the trigger plunger 40 ride over the shaft 22 during activation of the trigger 26.

 In Figures 10A-10B, the cannula 14 and the lead screw 50 are shown, respectively, before and after coring of the tissue. Figure 10A shows the cannula 14
30 in a fully retracted position with the lead screw 50 completely inside of the threaded portion of shaft 22. As the spline gear 36 is rotated the cannula 14 is advanced into the tissue 5. Figure 10B shows the cannula 14 and the lead screw 50 fully extended. The length of travel of the cannula 14 is limited by the length of the lead screw 50 and the length of the shaft 22. It is possible in the current invention to have different
35 sizes of biopsy devices 10 including different diameters and lengths of the cannula

5 14, corresponding shaft 22, and the lead screw 50 to provide different diameters and length core samples. In Figures 10A-10B the trigger 26 is shown in a locked position forward of a pair of trigger lock ramps 34.

In Figures 10C-10F, the device 10 is shown in the following stages: partial deployment of the trigger 26, Figure 10C; full deployment of the trigger 26,
10 Figure 10D; during return of the trigger 26, Figure 10E; and after complete transection of the tissue lesion 7 has taken place, Figure 10F. To deploy the garrote wire 74 a lock depressor 42 (Shown in Figure 9) depresses the trigger lock ramps 34 allowing the trigger body 24 to ride over and down the ramps 34. When the triggers 26 are activated, the trigger body 24 slides along the pair of trigger rods 30. The
15 trigger body 24 interfaces with the trigger plunger 40 pushing the trigger plunger 40 down the shaft 22, thereby pulling the ends of the garrote wire 74, which is attached to the trigger plunger 40 and spring plunger 48, and closing the looped section 75 (not shown) of the garrote wire 74 around the tissue lesion 7. In Figure 10C, the trigger 26 is only partially deployed and the spring 46 is expanded. In Figure 10D,
20 the trigger 26 is fully deployed and the spring 46 is then compressed. As shown in Figures 10D and 10E, the spring 46 keeps tension on the spring plunger 48 while the trigger 26 is reset for another pull on the garrote wire 74. In this embodiment the trigger 26 may be oscillated an unlimited number of times until the garrote wire 74 successfully makes the transection. Multiple oscillations of the trigger 26 enable the
25 actions of the garrote wire 74 to act as a saw on the tissue for cutting difficult tissue. In an alternative embodiment of device 10, the spring 46, the stop ring 38, and the spring plunger 48, present in the device 10 shown in Figure 9, may be absent from the device 10 allowing for only a one time activation of the trigger 26 and the garrote wire 74. This is accomplished by attaching both ends of the garrote wire 74
30 to the trigger plunger 40.

Figure 10F shows the device 10 after a completed tissue transection. After the transection is complete the cannula 14 and the device 10 are retracted from the biopsy site to retrieve the tissue sample present within the cannula 14.

Figure 11 shows an alternative embodiment of a cutting mechanism
35 located within the cannula 14 in place of the garrote wire 74. The cutting

5 mechanism 120 comprises a semi-circular inner blade 114 and a semi-circular outer blade 116 connected by a pair of pivot pins 118 which are supported by a pair of actuation rods 112. Alternatively the inner blade 114 and the outer blade 116 may be elliptical in shape. The inner blade 114 and the outer blade 116 are supported on a pair of curved cam surfaces 110 that are mounted or molded internally within
10 cannula 14. In operation, the cutting mechanism 120 is actuated by pulling the actuation rods 112, thereby forcing the inner blade 114 and the outer blade 116 to follow the cam surface 110 and pivot in an upward direction toward each other. This actuation is made after the cannula 14 is advanced to a desired location. Alternatively, the cutting mechanism 120 may also be used to core a section of
15 tissue 5 and lesion 7 by applying a longitudinal and/or rotational force to the cannula 14 attached to the inner blade 114 and the outer blade 116 in their un-pivoted states.

In Figures 12A-12B an alternative sleeve mechanism for activating the garrote wire 74 of the biopsy device 10 is shown generally at 100. The sleeve mechanism 100 comprises a split ring inner sleeve 102 and an outer sleeve 104
20 mounted around the shaft 22 of the biopsy device 10. The first end 79 of garrote wire 74 is connected to the inner sleeve 102 and the second end 81 of garrote wire 74 is connected to the outer sleeve 104. In Figure 12A the mechanism 100 is shown in a pre-deployment state with the inner sleeve 102 housed within the outer sleeve 104 and in an expanded state. In use, the garrote wire 74 is activated by pulling the
25 trigger 26 which first pulls down on both the inner sleeve 102 and the outer sleeve 104 simultaneously thereby placing an even force on both the first and second ends, 79,81, of the garrote wire 74. As the inner and outer sleeves, 102, 104, are pulled past a shoulder 106 of the shaft 22, as shown in Figure 12B the inner sleeve 102 allows the outer sleeve 104 to be pulled over the inner sleeve 102. The inner sleeve
30 102 is allowed to contract after it clears shoulder 106. The inner sleeve 102 is now pulled in an opposite direction against the shoulder 106. Alternatively, both the inner and outer sleeves 102, 104 can be replaced by a single sleeve resulting in an even pull on the garrote wire 74. The need to increase the force on the garrote wire 74 to increase the transection force is determined by the density of the lesion 7 and
35 tissue 5 encountered during the transection. The density of the lesion 7 and the

5 tissue 5 may change as the transection is made through additional layers of tissue, and thus the device as shown in Figures 12A-12B allows for changes in the force applied to the garrote wire 74 during the transection process.

In Figures 13A- 13B an alternative split sleeve garrote wire mechanism of the biopsy device 10 is shown generally at 128. As shown in Figure 13A, the split
10 sleeve mechanism 128 comprises a first sleeve half 120 and a second sleeve half 122 mounted around the shaft 22 of the biopsy device 10. As shown in Figure 13B, the first and second sleeve halves 120, 122 are mounted on to the shaft 22 in such a way that they are independently movable up and down the shaft 22, but are not independently rotatable on the shaft 22. An outside geometry 130 of the shaft 22
15 and a corresponding inside geometry 132 of the first and second sleeve halves 120, 122 prevent the first and second sleeve halves 120, 122 from rotating around the shaft 22. The geometries 130, 132 may be any non-circular shape thereby preventing the first and second sleeve halves 120, 122 from rotating around the shaft 22.

20 In Figure 13A the first end 79 of the garrote wire 74 is connected to the first sleeve half 120 and the second end 81 of the garrote wire 74 is connected to the second sleeve half 122 such that the first and second ends 79, 81 of the garrote wire 74 move when the first and second sleeve halves 120, 122 move up and down the shaft 22. Connected to the first sleeve half 120 is a first lever 126 and connected to
25 the second sleeve half 122 is a second lever 124 for moving the sleeve halves 120, 122 up and down the shaft 22. In operation, the first and second levers 126, 124 may be moved simultaneously pulling equally on the first end 79 and the second end 81 of the garrote wire 74. The first and second levers 126, 124 may also be moved independently creating different forces on the first end 79 and the second end 81 of
30 the garrote wire 74. The first and second lever 126, 124 may also be alternatively moved together and independently to create an alternating force on the first end 79 and the second end 81 of the garrote wire 74. The different movements of the first and second levers 126, 124 may be made at different times during the transection of the tissue by the garrote wire 74 depending on the density of the tissue being cut and

5 the force needed to successfully transect that tissue. Thus, the mechanism provides for oscillatory movement of the garrote wire 74, creating a sawing action.

In Figure 14 an alternative sleeve/spring garrote wire activation mechanism of the biopsy device 10 is shown generally at 150. The activation mechanism 150 comprises a first sleeve 152 and a second sleeve 154 mounted around shaft 22.

10 Connected to the first sleeve 152 is the first end 79 of the garrote wire 74. Connected the second sleeve 154 is the second end 81 of the garrote wire 74. The first sleeve 152 is connected to the second sleeve 154 by a spring 156. Alternatively, the spring 156 may consist of a plurality of springs (not shown). In use, the second sleeve 154 is moved down the shaft 22 by a lever mechanism similar

15 to the first and second levers shown in Figure 13, thereby pulling on both the second end 81 of the garrote wire 74 and pulling on the first sleeve 152 through the connection of the spring 156. The movement on the first sleeve 152 and the corresponding connected first end 81 of the garrote wire 74 is dependent on a spring force constant of the spring 156. The lower the spring force constant of the spring

20 156 the less initial movement of the first sleeve 152 takes place due to stretch of the spring 156. As the spring 156 is stretched to its limit the movement of the first sleeve 152 becomes equal to a rate of movement of the second sleeve 154. Alternatively, if the spring force constant of the spring 156 is set sufficiently high the first and second sleeves, 152, 154 may move together initially until the spring

25 force is overcome by the lesion 7 resistance to the cutting action of garrote wire 74 acting on the second sleeve 154 and then the first and second sleeves 152, 154 may move independently while the spring 156 is stretched and then finally the first and second sleeves 152, 154 may move together again after the spring 156 has been stretched completely. Alternatively the spring 156 may initially be placed in

30 compression by initially pulling on the first sleeve 152 thereby compressing the spring 156 between the first sleeve 152 and the second sleeve 154. This alternative creates an initial force less than the spring force on the first end 81 of the garrote wire 74 until the spring 156 compresses and then both the first and second ends 81, 79 of the garrote wire 74 move together as both the first and second sleeves, 152,

35 154 are moved together down the shaft 22. The alternating mechanism 150 creates

5 an oscillating action allowing for differing forces to be applied to the garrote wire 74 during the transection of different density tissue.

In Figure 15 an alternative spool mechanism for activating the garrote wire 74 is shown generally at 170. The mechanism 170 includes a garrote wire feed out spool 174, a washer 178, a snap ring 176, a guide collar 172, and a take up spool 10 173, mounted on the lead screw 50 at the proximal end 88 of the shaft 22. The first end 79 and a length of the garrote wire 74 (not shown) is coiled around the feed out spool 174 and is released from the feed out spool 174 as the second end 81 of the garrote wire 74 connected to the take up spool 173 is pulled and wrapped around the take up spool 173 when the take up spool 173 is rotated by the lead screw 50. The 15 take up spool 173 is rotated thereby pulling the garrote wire 74 through the lesion 7 surrounded by the looped section 75 of the garrote wire 74 thereby creating a saw like action on the lesion 7. The take up spool 173 is rotated until a successful transection of the lesion 7 has been completed.

20 The invention has been described in an illustrative manner, and it is to be understood that the terminology that has been used is intended to be in the nature of words of description rather than of limitation. Obviously, many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims the 25 invention may be practiced otherwise than as specifically described.

5

CLAIMS

We claim:

1. A biopsy device comprising:
 - a retractable stylet having a tip containing a plurality of blades and a central
 - 10 passage for receiving a localization needle;
 - a cannula connected to a drive mechanism, said cannula having a shaft with a cutting ring opposite said drive mechanism and a plurality of disk blades mounted within said cannula;
 - 15 said drive mechanism for simultaneously rotating said cannula and moving said cannula in a direction parallel to a longitudinal axis of said cannula;
 - a garrote with a first end, a second end, and a cutting surface for performing
 - 20 a cut transverse to said longitudinal axis of said cannula, said garrote mounted adjacent to said cutting ring of said cannula;
 - a trigger for deploying said garrote, said trigger including a locking mechanism for preventing deployment of said garrote prior to movement of said
 - 25 cannula a predetermined distance; and
 - a localization needle having a guide wire mounted within said needle.
2. The biopsy device as recited in Claim 1, wherein said plurality of
- 30 disk blades comprises at least two disk blades, a distal disk blade and a proximal disk blade, said proximal disk blade containing a notch for receiving said garrote wire as it exits said cannula to form said cutting surface.

5 3. The biopsy device as recited in Claim 1, wherein said guide wire is movable within said localization needle.

 4. The biopsy device as recited in Claim 2, wherein said locking mechanism prevents deployment of said garrote until a cutting plane of said garrote
10 is beyond an end of said guide wire.

 5. The biopsy device as recited in Claim 2, wherein said guide wire includes a barb for anchoring one end of said guide wire in a tissue sample.

15 6. The biopsy device as recited in Claim 1, wherein said locking mechanism has a locked position and an unlocked position, in said locked position said trigger abuts a plurality of ramps that are depressed by a lock depressor during advancement of said cannula.

20 7. The biopsy device as recited in claim 6, wherein when said locking mechanism is in said unlocked position, said trigger can be retracted to deploy said garrote.

 8. The biopsy device as recited in Claim 1, further comprising a spring
25 mounted around said drive mechanism for applying resistance against said garrote wire.

 9. A method of removing a tissue sample with a biopsy device, the method comprising the steps of:

- 30 a.) inserting a localization needle into a tissue sample;
 b.) advancing a barbed guide wire out of a distal end of the localization needle to anchor the biopsy device in the tissue;
 c.) advancing a stylet and a cannula having a cutting surface over the localization needle into the tissue;
35 d.) advancing the cannula cutting surface to cut a core of tissue;

5 e.) unlocking a trigger of a garrote wire when a cutting plane of the garrote wire has been advanced passed anend of the guide wire; and

 f.) moving the trigger to activate the garrote wire thereby pulling tissue against a plurality of disk blades located within the distal end of the cannula and making a cut transverse to a direction of advancement of the cannula.

10

10. The method of Claim 9, wherein the cannula cutting surface is advanced by rotating rotation knob.

11. The method of Claim 9, wherein the trigger is moved away from the
15 cutting surface to activate the garrote wire.

12. A biopsy device for removing a tissue sample comprising:
 a retractable stylet having a tip containing a plurality of blades and a central
20 passage for receiving a localization needle;

 a cannula connected to a drive mechanism, said cannula having a shaft with a first and a second cam surface each supporting a cutting blade mechanism opposite said drive mechanism;

25

 said cutting blade mechanism comprising an outer blade connected to an inner blade by a first and a second pivot pin and a first and second actuation rod for pulling said inner and outer blades along said first and second cam surface, thereby closing said first blade against said second blade.

30

13. The biopsy device as recited in Claim 12, wherein said inner and said outer blade are elliptical in shape.

14. The biopsy device as recited in Claim 12, wherein said inner and said
35 outer blade are semicircular in shape

5

15. A method of removing a tissue sample with a biopsy device, the method comprising the steps of:

- a.) inserting a localization needle into tissue;
- b.) advancing a hooked guide wire out of a distal end of the localization
10 needle to anchor the biopsy device in the tissue;
- c.) advancing a stylet and a cannula having a cutting surface over the localization needle into the tissue;
- d.) activating a trigger by pulling two activation rods toward the proximal end of the cannula thereby moving an inner blade and an outer blade each
15 connected pivotally to the actuation rods against a cam surface and toward each other creating a shearing action between the blades for transecting the tissue;

16. The method of Claim 15, further comprising the step of coring the tissue by pushing the inner and outer blades against the tissue prior to transecting the
20 tissue by closing the blades.

17. A biopsy device comprising:

- a retractable stylet having a housing containing a plurality of blades and a central passage for receiving a localization needle;
- 25 said housing of said stylet having a circumference, a leading edge, and a center axis, said leading edge being a straight line at forty five degrees to said center axis;
- a cannula connected to a drive mechanism, said cannula having a shaft supporting a cutting ring opposite said drive mechanism and a plurality of disk
30 blades mounted within said cannula;
- said drive mechanism for simultaneously rotating said cannula and moving said cannula in a direction that is parallel to a longitudinal axis of said cannula;
- a garrote wire with a first end, a second end, and a cutting surface for performing a cut transverse to said longitudinal axis of said cannula, said garrote
35 wire mounted adjacent to said cutting ring of said cannula;

5

a trigger for deploying said garrote wire, said trigger including a locking mechanism for preventing deployment of said garrote wire; and
a localization needle having a guide wire mounted within said needle.

10 18. The biopsy device as recited in Claim 17, wherein said housing of said stylet comprises two symmetrical conical shaped halves for dilation of tissue during use, said halves of said housing being integrally connected to each other.

15 19. The biopsy device as recited in Claim 17, wherein said housing of said stylet is constructed of a plastic material.

20 20. The biopsy device as recited in Claim 17, wherein said plurality of blades of said housing of said stylet comprises two symmetrical blades each with a leading edge, said blades seated in said housing with said leading edge of said blades exposed beyond said leading edge of said housing for transecting tissue.

25 21. The biopsy device as recited in Claim 20, wherein said leading edge of said blades tapers in a curve from a maximum exposed portion at a distal end of said housing to a minimum exposed portion within said housing whereby said blades can transect a portion of tissue equal in width to said circumference of said housing.

22. A biopsy device comprising:
a retractable stylet having a tip containing a plurality of blades and a central passage for receiving a localization needle;
30 a cannula mounted on a drive mechanism, said cannula having a shaft supporting a cutting ring opposite said drive mechanism and a plurality of disk blades mounted within said cannula;
said drive mechanism for simultaneously rotating said cannula and moving said cannula in a direction that is parallel to a longitudinal axis of said cannula;

35

- 5 a garrote wire with a first end, a second end, and a loop cutting surface for performing a cut transverse to said longitudinal axis of said cannula;
 an inner and an outer sleeve mounted around a shaft of said drive mechanism, said first end of said garrote wire attached to said inner sleeve and said second end of said garrote wire attached to said outer sleeve;
- 10 a localization needle having a guide wire mounted within said needle.

23. The biopsy device as recited in Claim 22, further comprising a trigger mechanism mounted adjacent said shaft of said drive mechanism for moving said inner and said outer sleeve.

15


24. The biopsy device as recited in Claim 22, further comprising a shoulder in said shaft of said drive mechanism for preventing movement of said inner sleeve beyond a predetermined distance, whereby said inner and outer sleeves are initially moved simultaneously by pulling equally on said first and second ends
- 20 of said garrote wire until said inner sleeve is stopped on said shoulder thereby ceasing movement of said first end of said garrote wire and continuing movement of said second end thereby increasing the force applied to said loop cutting surface for transecting the tissue.

- 25 25. A method of tissue removal with a biopsy device, the method comprising the steps of:

- a.) inserting a localization needle into tissue;
- b.) advancing a hooked guide wire out of a distal end of the localization needle to anchor the biopsy device in the tissue;
- 30 c.) advancing a stylet and a cannula over the localization needle into the tissue;
- d.) activating a trigger to pull an inner and an outer sleeve connected to the ends of a garrote wire thereby pulling a loop of the garrote wire around the tissue for transection;

5 e.) continuing activation of the trigger after the inner sleeve ceases movement thereby continuing to pull only the outer sleeve and one of the ends of the garrote wire to increase the force on the loop of the garrote wire transecting the tissue.

10 26. A biopsy device comprising:
a retractable stylet having a tip containing a plurality of blades and a central passage for receiving a localization needle;
a cannula mounted on a drive mechanism, said cannula having a shaft supporting a cutting ring opposite said drive mechanism and a plurality of disk
15 blades mounted within said cannula for cutting suspect breast tissue;
said drive mechanism for simultaneously rotating said cannula and moving said cannula in a direction that is parallel to a longitudinal axis of said cannula;
a garrote wire with a first end, a second end, and a loop cutting surface for performing a cut transverse to the longitudinal axis of the cannula;
20 a first and second sleeve mounted around a shaft of said drive mechanism, said first end of said garrote wire attached to said first sleeve and said second end of said garrote wire attached to said second sleeve;
a spring with a first end and a second end mounted around said shaft of said drive mechanism, said first end of said spring connected to said first sleeve and said
25 second end of said spring connected to said second sleeve, said spring applying a force to said first and second ends of said garrote wire; and
a localization needle having a guide wire mounted within said needle.






Fig-2A




Fig-2B






Fig-2C

Fig-3Fig-4




Fig-5




Fig-6

5/12




Fig-7




Fig-8




Fig-9

Fig-10A




Fig-10B




Fig-10C




Fig-10D




Fig-10E





Fig-10F






Fig-11




Fig-12A




Fig-12B




Fig-13A




Fig-13B




Fig-14




Fig 15

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 April 2002 (25.04.2002)

PCT

(10) International Publication Number
WO 02/032293 A3

(51) International Patent Classification⁷: **A61B 10/00**

(21) International Application Number: PCT/US01/47317

(22) International Filing Date: 3 October 2001 (03.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/692,928 20 October 2000 (20.10.2000) US
09/776,444 2 February 2001 (02.02.2001) US

(71) Applicant: **IMAGYN MEDICAL TECHNOLOGIES CALIFORNIA, INC.** [US/US]; One Park Plaza, Suite 110, Irvine, CA 92614 (US).

(72) Inventors: **WORM, Dustin**; 6116 Duernsey Lake Road, Delton, MI 49046 (US). **FLATLAND, Martin**; 533 Grand Pre, Kalamazoo, MI 49006 (US). **TOMANDL, Mark**; 436

W. Colfax Street, Hastings, MI 49056 (US). **PENROD, Mark, A.**; 150 Pifer Road, Delton, MI 49046 (US). **LUN, Warren, D.**; 175 South Kendall Street, Battle Creek, MI 49015 (US).


(74) Agents: **HONAKER, William, H.** et al.; Howard & Howard Attorneys, P.C., 39400 Woodward Avenue, Suite 101, Bloomfield Hills, MI 48304-5151 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: **INCISIONAL BREAST BIOPSY DEVICE**



(57) Abstract: A biopsy device (10) is provided which includes a localization needle (62) having a guide wire (66) preloaded into the biopsy device. The device includes a stylet (18) having a blade (16, 17) for transecting and separating tissue. The device further includes a cannula (14) for cutting a core of tissue and a garrote wire (74) for cutting a transection of tissue transverse to the core cut by the cannula. The garrote wire is activated by a trigger mechanism (26) which is locked out by a lockout feature within the device until the garrote wire has been advanced around the core of tissue cut by the cannula.

WO 02/032293 A3



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
17 April 2003

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US01/47317**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(7) :A61B 10/00

US CL :G00/564

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : G00/562, 564, 566, 567, 568; G06/167, 170

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

search terms: biopsy, cannula, stylet, blade, localization wire, guide wire, garrote, trigger, locking mechanism, core

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,353,804 A (KORNBERG et al) 11 October 1994, see entire document.	1-26
A	US 6,036,657 A (MILLIMAN et al) 14 March 2000, see entire document.	1-26
A	US 6,077,231 A (MILLIMAN et al) 20 June 2000, see entire document.	1-26
A	US 6,080,114 A (RUSSIN) 27 June 2000, see entire document.	1-26

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"G" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

14 MARCH 2002

Date of mailing of the international search report

02 JAN 2003

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CHARLES MARMOR, II

Telephone No. (703) 308-0858